

AD 330

Doosan
Mecc Alte
D+ &



ISO8528	GC,) &
SZUTEST	GC - \$\$\$
CE	

2000/14/EC
 &\$\$\$(#
 z) \$ z'z' D:

	"	kw	"	kw	Amp
400/230	330,00	264,00	300,00	240,00	433,00

fP GDE GC,) &
 fDF DE %s1 % %& GC" \$(** z&(GC

Standard Specifications

z
 fl ! E
 z
 z

ALTERNATOR

D: A Z'5JF

fl t
 fl " t
 fP \$\$# \$\$\$ t

TRANSFER SWITCH

t

AD 330

Doosan
Mecc Alte
D+' &'

Manufacturer		Doosan		
Model		P126TI-II		
		% \$ \$ ' "# "		
		294,00 kw [394,00HP]		
	L	11,050		
	"	123 x 155		
		17,0:1		
	fl # 7	"# "	1500	
	fl 7	L	23,00	
		L	65,00	
AbsorbedAirDischargeReSourceKey.Text	' # "	20,10		
	' # "	295,00		
fl ' # 7	' # "	47,40		
	° C	590,00		
		24 V d.c.		
	Load	% \$ \$ i	'+) i) \$ i
	# "			
		63,10	47,00	31,30

		Mecc Alte		
		ECO 38-2LN/4		
	Hz	50		
	"	300,00		
7cg'		0,80		
		3		
	fl 7	400/230		
	A	433,00		
Temperature		H		

		fl 7		fl 7	
	"	"	"	"	L
AD 330	2375,00	2950,00	1300,00	1588,00	450,00
		fl 7		fl 7	
	"	"	"	"	L
MS 60	3065	3960	1356	2097	470

AD 330

Doosan
Mecc Alte
D+' &'

f@z@Bl
f@z@Bl

"z" "z"

f@z@Bl

971

#

#

#

#

#

6G'9B'*\$-\$)'\$

6G'9B'*\$\$\$!*!&

6G'9B'*\$\$\$!*!(

f&%) +L

f&)(, L

f&% \$L

GA 8

!&+""

%, !&*(

&(\$)

ž

ž

ž

ž

AD 330

Doosan
Mecc Alte
D+ & "



- 1 Steel structures.
- 2 Emergency stop push button.
- 3 Control panel is mounted on the baseframe . Located at the right side of the generator set.
- 4 Corrosion-resistant locks and hinges.
- 5 oil could be drained via valve and a hose
- 6 Exhaust system in the canopy.
- 7 special large access doors for easy maintenance
- 8 in front and back side special large access doors for easy maintenance
- 9 Base frame -fuel tank.
- 10 Lifting points similar to ISO container , located on each top corner of the canopy
- 11 the canopy provides easy access to radiator cap.
- 12 sound proofing materials
- 13 Plastic air intake pockets.

	"	1356
fl "L	"	3960
fl "L	"	2097
	L	470